



The INSTALLER ADJUSTABLE HINGE is a unique product in the way you can obtain 4mm of linear adjustment in order to toe and heel a door or generally adjust, without removing the door sash from the frame. This adjustment is carried out by simply opening the door to 90°, and rotating the two adjuster cams on each hinge with a screwdriver until the desired amount of adjustment is obtained.

The INSTALLER ADJUSTABLE HINGE has been tested to BS7352:1990, class 8 severe rating , and achieved in excess of 175,000 cycles on endurance at 80 kg per single hinge

All sash components are available for PVCu profiles ie. flat, 5°, 10°, 15°. Personalized logo's on the underside of the sash component can be cast Subject to minimum agreed order quantities.

Euro groove versions are now available for most systems with a variation for composite doors.

Technical Data.

OPTION 1

Non security hinge pin for
open in doors.

OPTION 2.

Security hinge pin with a concealed grub screw for retention, suitable for open out doors.

FIXING.

Suitable for fitting to variable
sash profile with flat, 5°, 10°
15° available. Finished of with
push in covers.

FINISH.

Powder coated
Brown or White
Light Oak to Special Order.
Polished Gold to Special
Order

CONSTRUCTION

Hinge components in Zinc Alloy to BS1004 B
The hinge pin in steel,Zinc and yellow pass.

THE INSTALLER HINGE

IMPORTANT
ALWAYS ENSURE THAT HINGE
PIN IS FULLY INSERTED FROM
THE TOP BEFORE USE.

ALSO:
TOTAL ADJUSTER ROTATION
IS ONLY 90° CLOCKWISE,
OR 90° ANTI-CLOCKWISE
FROM CENTRAL POSITION.
FIT PUSH IN COVERS.

NOTE
ENSURE THAT ADJUSTERS
ARE SET IN PHASE THUS:

USING A SUITABLE SCREWDRIVER (POZI No2)
ROTATE BY SMALL AMOUNTS.
EACH ADJUSTER IN TURN TO
OBTAIN DESIRED SETTING

