

reXon 111 Hi-Grade Silicone

PRODUCT INFORMATION



This high-quality neutral silicone stays elastic and water resistant, and achieves universal adhesion* without primer on metals, wood, stone and masonry, as well as synthetic materials such as plastic (PVC, polycarbonate and plexi). That makes it ideal for sealing joints and junctions in a multitude of construction projects in buildings, cars, boats and caravans.

*reXon 111 silicone does not stick to bitumen, polyethylene, PTFE or polypropylene.

- Easy to apply indoors and outdoors
- Water resistant
- Neutral, odourless and acid-free
- Excellent adhesion without primer
- Cannot be painted
- Permanent elasticity
- Retains original colour and is UV and weather resistant
- Withstands temperatures from -50°C to 150°C
- Meets ISO 11600 F in G2
- Application temperature: between 5°C & 40°C (do not apply when there is a risk of rain or frost)
- Skin forming time: 25 minutes (colours) or 10 minutes (clear) at 23°C and 50% relative humidity
- Hardening rate: 3mm in 24 hours at 23°C and 50% relative humidity
- 310ml tube



PART NUMBERS

Swatches				
Colour	White	Clear	Cream RAL9001	Agate Grey RAL7038
Part Code	SIL21000	SIL21006	SIL22003	SIL22008
Size	310ml tube	310ml tube	310ml tube	310ml tube
Box Qty	12	12	12	12