



FB-6200

23mm Wide Flush Bolts



PRODUCT INFORMATION



These finger-operated shoot bolts work to secure the slave leaf on double aluminium door assemblies. They are rebated into the leading edge or inside face of the door and operated by a lever which sits flush when the bolt is engaged and the door is closed. To ensure ease of operation, Axim FB series flush bolts have a deep finger recess and large lever. A standard installation requires two flush bolts morticed into the top and bottom of the door. For maximum security the Axim flush bolt has a hardened steel bolt, zinc plated with an anti-rattle sleeve.

- Smooth lever action flush bolts
- Radiused faced or flat faced available
- Mounted in the leading edge or inside face of the slave leaf of a pair of doors
- Manufacturer's guarantee: 30 months
- Available in one fully threaded length, 305mm (12") which can be cut to suit
- Silver satin chrome finish
- Shoot bolt: 18 mm diameter and a die cast zinc alloy body mechanism
- Fixings included

TECHNICAL DRAWINGS



PART NUMBERS

Face Plate	Length	Part Code	Box Qty
Radius Face	305mm	AFB620112R	1
Square Face	305mm	AFB620112F	1



FB-6200 Series Flush Bolt Extension Rods

PRODUCT INFORMATION



These extension rods work with the Axim FB-62 Series Flush Bolts to accommodate taller doors.

- Choose from 20" or 36" lengths
- 30 months manufacturer's guarantee


PART NUMBERS

Bar Length	Part Code
20 inch	AFB62200
36 inch	AFB62360



Flush Bolt Sprung Loaded Socket Keep

PRODUCT INFORMATION



This floor socket keep works with Axim FB-6200 and FB-6000 series flush bolts.

- Sprung loaded
- Dust resistant
- Satin chrome finish
- 30 months manufacturer's guarantee

PART NUMBERS

Height	Top Diameter	Bottom Diameter	Part Code
465mm	35mm	21.2mm	AFB62035