

# **Superglue Activator**



# SAFETY DATA SHEET BACT

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BACT

Container size 200ml, 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Activator.

1.3. Details of the supplier of the safety data sheet

Supplier Bondloc UK Ltd

Units 1 & 2 Bewdley Business Park

Long Bank Bewdley Worcestershire DY12 2TZ United Kingdom +44 (0)1299 269269 +44 (0)1299 269210 sales@bondloc.co.uk

1.4. Emergency telephone number

**Emergency telephone** +44 (0)1299 269269

#### SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 2 - H411

2.2. Label elements

**Pictogram** 







Signal word

Danger



Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H315 Causes skin irritation. H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Naphtha (Petroleum) Hydrotreated Light (Low Boiling Point), N,N-dimethyl-p-toluidine

Supplementary precautionary

ary P102 Keep out of reach of children.

statements

#### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

# 3.2. Mixtures

# Naphtha (Petroleum) Hydrotreated Light (Low Boiling Point)

30-60%

CAS number: 64742-49-0 EC number: 265-151-9

# Classification

Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

butane 10-30%

CAS number: 106-97-8 EC number: 203-448-7

# Classification

Flam. Gas 1 - H220



N,N-dimethyl-p-toluidine <1%

CAS number: 99-97-8 EC number: 202-805-4

Classification

Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

**General information** Move affected person to fresh air at once.

**Inhalation** Move affected person to fresh air at once. If breathing stops, provide artificial respiration.

Keep affected person warm and at rest. Get medical attention immediately.

**Ingestion** Do not induce vomiting. Rinse mouth. Move affected person to fresh air at once. Get medical

attention if any discomfort continues.

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get

medical attention. Remove contact lenses, if present and easy to do. Continue rinsing. Get

medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Prolonged and repeated contact with solvents over a long period may lead

to permanent health problems.

Inhalation May cause respiratory system irritation. Overexposure to organic solvents may depress the

central nervous system, causing dizziness and intoxication and, at very high concentrations,

unconsciousness and death.

**Ingestion** Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal

tract. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as

inhalation.

**Skin contact** May cause irritation. Prolonged skin contact may cause redness and irritation.

**Eye contact** May irritate eyes. Prolonged contact may cause redness and/or tearing.

# 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

# 5.2. Special hazards arising from the substance or mixture



Specific hazards Thermal decomposition or combustion products may include the following substances:

> Carbon oxides and other toxic gases or vapours Extremely flammable. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a

source of ignition and flash back.

Hazardous combustion

products

Irritating gases or vapours. Toxic gases or vapours. Highly flammable gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water spray to reduce vapours. Cool containers exposed to heat with water spray and

remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Ensure suitable respiratory protection is worn during removal of

spillages in confined areas.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand,

earth or other suitable non-combustible material.

# 6.3. Methods and material for containment and cleaning up

Absorb spillage with inert, damp, non-combustible material. Collect and place in suitable Methods for cleaning up

waste disposal containers and seal securely. Flush contaminated area with plenty of water.

Eliminate all sources of ignition. Provide adequate ventilation.

#### 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

# SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid contact with skin and eyes. Keep away from heat, hot

> surfaces, sparks, open flames and other ignition sources. No smoking. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. When sprayed

on a naked flame or any incandescent material the aerosol vapours can be ignited.

Advice on general occupational hygiene Good personal hygiene procedures should be implemented.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Flammable/combustible materials. Do not store near heat sources or expose to high

> temperatures. Keep container tightly closed, in a cool, well ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure Controls/personal protection



#### 8.1. Control parameters

# Occupational exposure limits

#### butane

Long-term exposure limit (8-hour TWA): WEL 600 ppm  $1450 \text{ mg/m}^3$  Short-term exposure limit (15-minute): WEL 750 ppm  $1810 \text{ mg/m}^3$  WEL = Workplace Exposure Limit

#### 8.2. Exposure controls

### Protective equipment







Appropriate engineering

controls

Provide adequate ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

The most suitable glove should be chosen in consultation with the glove

supplier/manufacturer, who can provide information about the breakthrough time of the glove

material.

Other skin and body

protection

Wear protective clothing.

Hygiene measures Provide eyewash station. Wash promptly if skin becomes contaminated. When using do not

eat, drink or smoke.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn.

#### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Clear.

Odour Characteristic.

Odour threshold No information available.

**pH** Not applicable.

Melting point No information available.

Initial boiling point and range No information available.

Flash point < -40°C

**Evaporation rate** No information available.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 1.8% Upper flammable/explosive limit: 9.5%

Vapour pressure Not applicable.

Vapour density No information available.

Solubility(ies) Not applicable.

Partition coefficient Not available.

Auto-ignition temperature 440-580°C



**Decomposition Temperature** No information available.

Viscosity <1 cps @ 25°C

**Explosive properties** No information available.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 603.3 g/l.

#### SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Exothermic reaction with: cyanoacrylates

10.2. Chemical stability

Stability Highly volatile

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or

direct sunlight. Do not pierce or burn, even after use.

10.5. Incompatible materials

Materials to avoid Keep away from flammable and combustible materials. No specific material or group of

materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Heating may generate the following products: Carbon dioxide (CO2). Carbon monoxide (CO).

Other toxic gases and vapours

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 33,333.3333333

Acute toxicity - dermal

**ATE dermal (mg/kg)** 100,000.0

Acute toxicity - inhalation

ATE inhalation (dusts/mists 1

1.5

mg/l)

Reproductive toxicity

Reproductive toxicity - fertility May damage fertility.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems.

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea. Inhalation of vapour or mist

may cause lung oedema. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness

and death.



**Ingestion** Drowsiness, discrientation, vertigo. Narcotic effect. Pneumonia may be the result if

vomited material containing solvents reaches the lungs.

**Skin contact** Irritating to skin. Prolonged or repeated exposure may cause severe irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health

hazards

Narcotic effect.

Route of exposure Inhalation Skin absorption

Target organs Central nervous system Respiratory system, lungs

# Toxicological information on ingredients.

# Naphtha (Petroleum) Hydrotreated Light (Low Boiling Point)

Acute toxicity - inhalation

ATE inhalation (gases

4,500.0

ppm)

ATE inhalation (vapours

mg/l)

11.0

ATE inhalation 1.5

(dusts/mists mg/l)

# SECTION 12: Ecological Information

**Ecotoxicity**The product contains substances which are toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.1. Toxicity

**Ecotoxicity** 

### 12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

# 12.3. Bioaccumulative potential

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces. The product is insoluble in water and will spread on the water surface. The product

contains volatile substances which may spread in the atmosphere.

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

# SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations



**Disposal methods** Do not puncture or incinerate, even when empty.

# SECTION 14: Transport information

# 14.1. UN number

UN No. (ADR/RID) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950 UN No. (ADN) 1950

# 14.2. UN proper shipping name

Proper shipping name

**AEROSOLS** 

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

# 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



# 14.4. Packing group

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Dangerous Preparations Directive 1999/45/EC.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### **Inventories**

#### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

#### **SECTION 16: Other information**

Revision date 03/10/2014

SDS number 4593

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: may burst if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin. H315 Causes skin irritation. H331 Toxic if inhaled. H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

WARRANTY: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is consider accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.

