

117 LMN Silicone

Perimeter sealing of windows & door frames..

This low modulus neutral oxime curing multi-purpose silicone sticks firmly without primer to most surfaces including PVC, treated wood, aluminium, steel and glass*, making it ideal for sealing joints in construction and engineering applications. With the use of a primer, 117 LMN can also be used with confidence on alkali surfaces such as concrete and brick.

*Xpert 117 LMN silicone is not recommended for use on insulated glass (can affect the butyl sealing) or security glass (can affect the PVB film).

- For use outdoors and indoors in well-ventilation rooms
- High resistance to ageing, UV, weather conditions, low and high temperatures
- Not suitable for applications in continuous contact with water
- Permanent elasticity
- Neutral oxime curing system
- Application temperature: between 5°C & 40°C (do not apply when there is a risk of rain or frost)
- Skin forming time: 25-30 minutes at 23°C and 50% relative humidity
- Hardening rate: 2.5mm in 24 hours at 23°C and 50% relative humidity



Colour	RAL	Size	Part Code	Box Qty.
Snow White	-	280ml	SIL20000	12
Clear	-	280ml	SIL20006	12
Brown	RAL8017	280ml	SIL20002	12
Black	RAL9005	280ml	SIL20005	12
Anthracite Grey	RAL7016	280ml	SIL20007	12

